

# Rubber Tracks Maintenance Checklist

*(Maintenance to be carried out before operating equipment)*

MAINTENANCE CHECKS	OK	Work Performed	Future Repair Required
Before use, ensure the rubber tracks have been installed correctly	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Daily check of the rubber tracks to ensure correct tension	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Check the rubber track tension after the first 30 hours, then every 50 hours thereafter	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Daily check of the rubber track tread & carcass for evidence of uneven wear, cuts, punctures, missing lugs or exposed cables	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Daily check of the undercarriage including sprockets, rollers and idlers for excessive wear or damage	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Daily check of the undercarriage including sprockets, rollers and idlers for any foreign objects such as rocks, clay, gravel and mud that may have become lodged. Remove objects before operating equipment	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Check rubber track and undercarriage for any evidence of oil, salt, fuel or other substances and remove	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

If you identify any issues with your Rubber Track contact DEKK on 1300 335 528 or [sales@dekktrack.com.au](mailto:sales@dekktrack.com.au) for assistance.